

8512 High Temperature Masking Tape	Ref: 8512	
--	------------------	---

1. Product Description / Application

Rev Dec 18

Green Polyester Masking Tape - 180°C

Our 9512 Green Polyester Tape is the industry standard for use when Powder Coating, E-Coating, Anodizing or Plating.

At 88 microns thick, our 8512 has a maximum temperature resistance of 180°C. A low tack silicone adhesive system ensures that the tape will leave no residue on the surface once removed and the high quality polyester film means the tape will not shrink in application.

2. Key Characteristics

- 88 microns thick
- 180°C temperature resistance
- A low tack silicone adhesive system ensures that the tape will leave no residue
- High quality polyester film means the tape will not shrink

4. Product Data

Temperature Resistance	180°C
Backing	50 Micron Polyester Film
Adhesive	Silicone
Thickness	38 microns
Total thickness	88 microns
Breaking Strength	8.9kg per cm
Elongation	90%
Adhesion to steel	0.35kg per cm
Dielectric strength	6500 volts

Important Notice

All UKIT products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning UKIT products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for UKIT products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.